

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claim 1 (Currently Amended): A fluorine-cleaned plasma~~Plasma~~ processing apparatus comprising:

- a chamber within which a substrate is processed in use;
- a first electrode formed from a nickel alloy having substantially planar upper and lower surfaces, wherein the substrate is placed for processing upon the upper surface of the first electrode;
- a second electrode;
- a heater for heating at least the first electrode to a processing temperature; and
- a power supply system arranged to cause an electrical discharge between the said first and second electrodes so as to produce the plasma in the chamber from one or more gases supplied to the chamber, characterized~~characterised~~ in that:

- the heater comprises one or more heating members arranged in a substantially planar manner, the heater and electrode forming an assembly such that the parts of the one or more heating members that are closest to the said upper surface of the first electrode, define a first plane that is separated from the upper surface by a distance Y, the parts of the one or more heating members that are furthest from the said upper surface of the first electrode, define a second plane, wherein the separation of the first and second planes defines a heater thickness X and wherein Y lies in the range 1.2X to 3X and in that the apparatus further comprises a gas delivery system comprising a fluorine-containing gas, the gas delivery system being configured to supply the fluorine-containing gas to the chamber during a plasma cleaning process.

Claim 2 (Original): Apparatus according to claim 1, wherein the heater is arranged within the first electrode and wherein the second plane is separated from the lower surface of the electrode by a distance W, wherein a thickness Z of the combined electrode and heater assembly is given by $Y+W+X$; and wherein Z lies in the range 2Y to 2.5Y and Y lies in the range 1.2X to 3X.

Claim 3 (Previously Presented): Apparatus according to claim 1, further comprising a heat shield, positioned at the bottom surface of the assembly so as to reduce heat dissipation from the bottom part of the assembly.

Claim 4 (Previously Presented): Apparatus according to Claim 1, wherein the nickel alloy comprises at least 99% by weight of nickel.

Claim 5 (Previously Presented): Apparatus according to Claim 1, wherein the first electrode is adapted in use to be heated to 700°C from ambient temperature within substantially one hour or less, preferably 45 minutes or less.

Claim 6 (Previously Presented): Apparatus according to Claim 1, wherein the first electrode is adapted to cool in use from 700 to 400°C in less than 30 minutes.

Claim 7 (Previously Presented): Apparatus according to Claim 1, wherein the heater comprises a tubular, rod-like or foil heater.

Claim 8 (Withdrawn): A method of plasma cleaning the contents of a plasma processing chamber according to Claim 1, the method comprising providing a fluorine-containing gas in the said chamber whilst the said first electrode is at an elevated temperature such that the first electrode is cleaned by the action of the fluorine-containing gas.

Claim 9 (Withdrawn): A method according to claim 8, wherein the method comprises, prior to the introduction of the gas, using the chamber to perform plasma processing upon a substrate heated to a processing temperature.

Claim 10 (Withdrawn): A method according to claim 8, wherein the first electrode is maintained at a predetermined temperature during cleaning.

Claim 11 (Withdrawn): A method according to claim 8, wherein the first electrode is allowed to cool during cleaning.

Claim 12 (Withdrawn): A method according to Claim 8, wherein the elevated temperature is at least initially at substantially the processing temperature.

Claim 13 (Withdrawn): A method according to Claim 8, wherein the elevated temperature is in the range 200°C to 800°C.

Claim 14 (Withdrawn): A method according to claim 13, wherein the temperature is in the range 400°C to 700°C.

Claim 15 (Withdrawn): A method according to Claim 8, wherein the fluorine-containing gas comprises a mixture of CF₄ and O₂ in the respective ratios of 80% to 20% by volume.

Claim 16 (Withdrawn): A method according to Claim 8, wherein the flow rate of the fluorine-containing gas is 150 standard cubic centimetres per minute.

Claim 17 (Withdrawn): A method according to Claim 8, wherein the plasma cleaning step is performed using a low frequency component of between 50kHz and 450 kHz, and/or high frequency component of 13.56 MHz.

Claim 18 (Withdrawn): A method according to Claim 8, wherein the plasma power range is between 50W and 300W.

Claim 19 (Withdrawn): A method of plasma processing comprising positioning a substrate in contact with the upper surface of the first electrode in a plasma processing chamber of plasma processing apparatus according to Claim 1, supplying one or more

process gases to the chamber and generating a plasma within the chamber from the process gas(es), using the first and second electrodes so as to plasma process the substrate.

Claim 20 (Withdrawn): A method according to Claim 8, wherein the plasma process comprises a deposition or etching process.

Claim 21 (Withdrawn): A method according to Claim 8, wherein the deposition is of an electrically insulating material.